

OSLO V 900 SWING (0,9 H2) R290

A
G
B
A
G
B
A
G
B
A
G
B

TN Chiller
 TB Freezer
 TB/TN Dual Temp
 TC Heated
 TC/TN Hot&Cold
 N Non-refrigerated
 RS - Static
 RV - Ventilated
 RS/TC S - Static and Dry Heat convertible
 RV/TC S - Ventilated / Dry Heat convertible
 HUR - Meat
 CH - Chocolate
 TC S - Dry Heat
 TC BM - Bainmarie
 N - Non-refrigerated

809607/1 | 809607/2 | 809607/3 | 809607/4

H 2000	2000	2000	2000
D 900	900	900	900
L 937	1250	1875	2500

3M1 sandwiches • dairy • drinks • delicatessen • fresh products

Installation

- Plug in

Configuration
 5 adjustable shelves
 Depth 450mm
Temperature range
 -1/+5°C

Refrigerant
 R290

Refrigeration
 Ventilated

Compressor
 Hermetic

Climate & product class
 3M1

Side panels
 25mm

Closing system
 Swing doors (tempered double glass
 4+10+4mm)

Lighting
 Optional (canopy and shelves)

Equipment handling
 Adjustable feet

Defrost
 Air



OSLO V 900 SWING D 937 (0,9 H2) R290	OSLO V 900 SWING D 1250 (0,9 H2) R290	OSLO V 900 SWING D 1875 (0,9 H2) R290	OSLO V 900 SWING D 2500 (2x1250) (0,9 H2) R290
809607/1	809607/2	809607/3	809607/4

External dimensions (LxDxH)	Sides 25mm thick	Adjustable feet Swivel casters	987x900x2000mm	1300x900x2000mm	1925x900x2000mm	2550x900x2000mm
	Sides / thick	Adjustable feet Swivel casters				
Net volume	Ventilated					
Weight (net)	R290					
Refrigeration	3					
Refrigerant	25 °C / 60 %RH					
Climate class	-1/+5°C					
Operating conditions	1 Hermetic	1 Hermetic	1 Hermetic	1 Hermetic		
Product temperature	Air					
Compressor (q.ty.-type)	230 V / 1 Ph / 50 Hz					
Defrost	584 W/ 2,86 A					
Power supply	601 W/ 2,94 A					
Electrical input (nominal)	649 W/ 3,18 A					
Electrical input (defrost)	783 W/ 3,84 A					
	0 W/ 0 A					
	0 W/ 0 A					
	0 W/ 0 A					
	0 W/ 0 A					

Technical sheet about models with condensing unit included with air / el. heater

Setup

Shelves dimensions (LxD)	930x450mm	1240x450mm	2pcx930x450mm	2pcx1240x450mm
	930x450mm	1240x450mm	2pcx930x450mm	2pcx1240x450mm
930x450mm	1240x450mm	2pcx930x450mm	2pcx1240x450mm	
930x450mm	1240x450mm	2pcx930x450mm	2pcx1240x450mm	
930x450mm	1240x450mm	2pcx930x450mm	2pcx1240x450mm	

Height	Length	Model type	Total display area (m2)	Temperature class	Recommended temperature (°C)	Energy class	Energy efficiency index EEI	Annual energy consumption kWh/A	Light source type and class
2000	937mm	Vertical	1,51	M1	+7°C	B	18,17	1918,80	/
	1250mm	Vertical	2,02	M1	+7°C	B	15,55	1972,64	/
	1875mm	Vertical	3,03	M1	+7°C	B	12,60	2132,79	/
	2500mm	Vertical	4,04	M1	+7°C	B	12,15	2572,16	/

Configuration: Vertical refrigerated show case plug in, closed with swing doors with five shelves defrosting-air

