

OSLO VSV 700 SLIDING (0,7 H1.5) R290

809505/11 | 809505/21 | 809505/31 | 809505/41

H 1500	1500	1500	1500
D 700	700	700	700
L 937	1250	1875	2500

3M1 sandwiches • dairy • drinks • delicatessen • fresh products

Installation

- Plug in

Configuration

3 adjustable shelves
Depth 150, 200, 250mm
Temperature range
-1/+5°C

Refrigerant

R290

Refrigeration

Ventilated

Compressor

Hermetic

Climate & product class

3M1

Side panels

25mm

Closing system

Sliding doors

Lighting

Optional (canopy and shelves)

Equipment handling

Adjustable feet

Defrost

Air

AGB TN TB TB/TN TC TC/TN N
Chiller Freezer Dual Temp Heated Hot&Cold Non-refrigerated

RS - Static
RV - Ventilated
RS/TC S - Static and Dry Heat convertible
RV/TC S - Ventilated / Dry Heat convertible
HUR - Meat
CH - Chocolate
TC S - Dry Heat
TC BM - Bainmarie
N - Non-refrigerated



OSLO VSV 700 SLIDING 937 (0,7 H1.5) R290	OSLO VSV 700 SLIDING 1250 (0,7 H1.5) R290	OSLO VSV 700 SLIDING 1875 (0,7 H1.5) R290	OSLO VSV 700 SLIDING 2500 (0,7 H1.5) R290
809505/11	809505/21	809505/31	809505/41

External dimensions (LxDxH)	Sides 25mm thick	Adjustable feet	987x700x1500mm	1300x700x1500mm	1925x700x1500mm	2550x700x1500mm
		Swivel casters				
External dimensions (LxDxH)	Sides / thick	Adjustable feet				
		Swivel casters				
Net volume			151,79 dm3	202,50 dm3	303,75 dm3	405,00 dm3
Weight (net)			173 kg	231 kg	347 kg	463 kg
Refrigeration	Ventilated					
Refrigerant	R290					
Climate class	3					
Operating conditions	25 °C / 60 %RH					
Product temperature	-1/+5°C					
Compressor (q.ty-type)	1 Hermetic	1 Hermetic	1 Hermetic	1 Hermetic	1 Hermetic	1 Hermetic
Defrost	Air					
Power supply	230 V / 1 Ph / 50 Hz					
Electrical input (nominal)	584 W/ 2,86 A	601 W/ 2,94 A	649 W/ 3,18 A	783 W/ 3,84 A		
Electrical input (defrost)	0 W/ 0 A	0 W/ 0 A	0 W/ 0 A	0 W/ 0 A		

Technical sheet about models with condensing unit included with air / el. heater

Setup

Shelves dimensions (LxD)

930x150mm	1240x150mm	2pcx930x150mm	2pcx1240x150mm
930x200mm	1240x200mm	2pcx930x200mm	2pcx1240x200mm
930x250mm	1240x250mm	2pcx930x250mm	2pcx1240x250mm

Height	Length	Model type	Total display area (m2)	Temperature class	Recommended temperature (°C)	Energy class	Energy efficiency index EEI	Annual energy consumption kWh/A	Light source type and class
1500	937mm	Semivertical	0,97	M1	+°C	B	16,21	1705,60	/
	1250mm	Semivertical	1,30	M1	+°C	B	16,59	1972,64	/
	1875mm	Semivertical	1,95	M1	+°C	B	14,58	2132,79	/
	2500mm	Semivertical	2,60	M1	+°C	B	14,82	2572,16	/

Configuration: Semivertical refrigerated show case plug in, closed with sliding doors with three shelves defrosting-air

